

Coaxial Panel Connector 22_SMC-50-0-3/111_N

Description

Straight bulkhead receptacle jack

Interface standards

IEC 60169-9_MIL-STD-348A/312_CECC 22140



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 10 GHz

Mechanical Data

Number of matings 500
Weight 0.0011 kg

Environmental Data

Operating temperature -65 °C to 165 °C
2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (Nickel underplated)
Washer	Bronze	Gold Plating (Nickel underplated)

Related Documents

Catalogue drawing DCA-00011570
Mounting hole DOU-00008855

Ordering Information

Single package 22_SMC-50-0-3/111_NE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[22_SMC-50-0-3/111_NE](#)