

Up Converter Frequency Mixer

SIM-U712H+

Level 17 (LO Power +17 dBm) 10 to 7100 MHz



Generic photo used for illustration purposes only

CASE STYLE: HV1195

Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
IF Power	100mW
For extended temperature range, consult factory. Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	2
IF (IN)	8
RF (OUT)	4
GROUND	1,3,5,6,7

Features

- up converter mixer
- low conversion loss, 7.3 dB typ.
- high IP3, 27 dBm typ.
- ceramic, tiny size
- aqueous washable
- protected by US patent, 7,027,795

Applications

- cellular infrastructure
- WIMAX
- line-of-sight links
- wide band receivers

+RoHS Compliant


The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications




Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	10, 20, 50, 100, 200, 500

Outline Drawing



PCB Metal Land Pattern




Suggested Layout. Tolerance to be within ±.002

Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
.200	.180	.087	.025	.050	.028	.043
5.08	4.57	2.2098	0.64	1.27	0.71	1.09
H	J	K	L	M	N	wt
.050	.030	.043	.204	.127	0.065	grams
1.27	0.76	1.09	5.18	3.23	1.65	0.08

Demo Board MCL P/N: TB-382 Suggested PCB Layout (PL-239)



- NOTES:
1. TRACE WIDTH AND GAP ARE SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .020 ±.0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED.
 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

Electrical Specifications

FREQUENCY (MHz)			CONVERSION LOSS* (dB)			LO-IF (IN) ISOLATION (dB)		LO-RF (OUT) ISOLATION (dB)		IP3 at center band (dBm)
IF (IN)	LO	RF (OUT)	Typ.	σ **	Max.	Typ.	Min.	Typ.	Min.	Typ.
2600-7100	10-1780	2600-7100	7.3	0.3	9.5	27	14	19	11	27

1 dB Compression: +14 dBm typ.


* Conversion Loss at 30 MHz LO

** σ is a standard deviation

Typical Performance Data

Frequency (MHz)	Conversion Loss (dB)		VSWR RF Port (:1)		Frequency (MHz)	Isolation L-I (dB)		Isolation L-R (dB)		VSWR LO Port (:1)
	LO	RF (OUT)	LO +17dBm	LO +17dBm		LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	
2600.10	30.00	2630.10	7.80	1.34	11.00	67.68	51.44	1.47		
2800.10	30.00	2830.10	7.15	1.41	51.00	55.46	42.85	1.50		
3000.10	30.00	3030.10	6.88	1.59	91.00	50.53	38.59	1.50		
3200.10	30.00	3230.10	6.61	1.52	153.60	46.33	35.04	1.53		
3400.10	30.00	3430.10	6.74	1.60	238.80	42.47	31.79	1.55		
3600.10	30.00	3630.10	6.62	1.69	324.00	39.73	29.14	1.59		
3800.10	30.00	3830.10	6.81	1.91	409.20	37.68	27.14	1.60		
4000.10	30.00	4030.10	7.00	2.30	494.40	35.96	25.30	1.58		
4400.10	30.00	4430.10	7.21	2.77	664.80	33.22	22.36	1.52		
4600.10	30.00	4630.10	7.42	2.80	750.00	31.84	21.29	1.49		
4800.10	30.00	4830.10	7.52	3.53	776.67	31.61	21.20	1.53		
5000.10	30.00	5030.10	7.64	3.83	803.33	31.30	21.00	1.54		
5400.10	30.00	5430.10	7.58	2.09	871.67	30.30	20.66	1.67		
5600.10	30.00	5630.10	7.45	1.43	913.33	29.80	20.50	1.69		
5800.10	30.00	5830.10	7.59	1.78	955.00	29.17	20.11	1.79		
6280.10	30.00	6310.10	8.08	1.46	1080.00	27.50	19.86	1.93		
6440.10	30.00	6470.10	7.68	1.23	1121.67	26.99	19.53	2.10		
6600.10	30.00	6630.10	7.98	1.49	1205.00	25.85	19.07	2.23		
6920.10	30.00	6950.10	7.75	2.82	1436.67	23.03	17.93	2.37		
7240.10	30.00	7270.10	8.80	3.39	1796.50	19.26	16.94	2.29		

Electrical Schematic










Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. C
ECO-000060
SIM-U712H+
ED-12399/5
DJ/TD/CP/AM
200821
Page 1 of 2



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

